

Modelo	Tonelaje	Garganta	Punzonado diámetro/espesor	Doblez (opcional)	Corte de Ángulo	Escotado	Corte de Barra Redonda	Corte de Barra Cuadrada	Corte de Solera	Velocidad (golpes por min.)
P-50	50	5"	13/16" en 3/4" * 1-1/4" en 1/2" * 2-1/2" en 1/4"	6" y 12" de largo	3" x 3" x 3/8" 3-1/2" x 3-1/2" x 5/16"	40 tons 2-1/4" x 3" x 1/4"	Opcional 1/4" a 1-3/8"	Opcional 1/2" a 1"	13" x 1/4" 12" x 3/8" 10" x 1/2" 6" x 3/4"	30 en 1/2"
P-65	65	8"	1-1/16" en 3/4" * 1-5/8" en 1/2" * 3-1/4" en 1/4"	8", 12", 14", y 24" de largo	5" x 5" x 3/8" 4" x 4" x 1/2"	56 tons 2-3/4" x 4" x 1/4"	1/4" a 1-1/2"	1/2" a 1"	15" x 5/8" 10" x 3/4"	30 en 3/4"
P-90	90	10"	1-1/8" en 1" * 2-1/4" en 1/2" * 4-1/2" en 1/4"	12" y 24" de largo	5" x 5" x 1/2"	75 tons 3-1/2" x 5" x 3/8"	1/2" a 2"	1/2" a 1-3/8"	18" x 1/2" 12" x 3/4" 8" x 1"	32 en 3/4"
P-110	110	12"	1-7/16" en 1" * 2-3/4" en 1/2" * 5" en 1/4"	12" y 24" de largo	6" x 6" x 5/8"	95 tons 4" x 6" x 3/8"	1/2" a 2"	1/2" a 1-3/8"	20" x 1/2" 18" x 3/4" 12" x 1"	30 en 3/4"
P-140	140	12"	1-3/4" en 1" * 3-1/2" en 1/2" * 5" en 1/4"	12" y 24" de largo	6" x 6" x 5/8"	95 tons 4" x 6" x 3/8"	1/2" a 2"	1/2" a 1-3/8"	20" x 1/2" 18" x 3/4" 14" x 1"	30 en 3/4"
PII-88 Doble operador	88	9"	1-1/16" en 1" * 2" en 1/2" * 4-1/4" en 1/4"	24", 36" y 48" de largo	5" x 5" x 3/8" 4" x 4" x 1/2"	56 tons 2-3/4" x 4" x 1/4"	1/4" a 1-1/2"	1/2" a 1"	24" x 1/4" 12" x 5/8" 8" x 3/4"	19 en 1"
PII-140 Doble operador	140	20.5"	1-3/8" en 1-1/4" * 3-1/2" en 1/2" * 5" en 1/4"	18", 24", 36" y 48" de largo	6" x 6" x 5/8"	95 tons 4" x 6" x 3/8"	1/2" a 2"	1/2" a 1-3/8"	20" x 1/2" 18" x 3/4" 14" x 1"	24 en 1"
SEP-120 Punzonadora	120	21.5"	1-1/2" en 1" * 3" en 1/2" * 5" en 1/4"	18" de largo	N/A	N/A	N/A	N/A	N/A	16 en 1"

* Requiere herramental especial