

Serie NC (Control NC)								
Serie	Modelo	Capacidad máxima			Largo máx. del tubo con mandril	Radio máx. de dobléz	Ángulo máx. de dobléz	Peso (kg)
		Tubo redondo (Acero suave) Ø x espesor	Tubo redondo (Acero inoxidable) Ø x espesor	Tubo rectangular (Acero suave) largo x ancho x espesor				
NC	SB-38NC	38.1 mm x 2 mm (1.5" x 0.07")	38.1 mm x 1.4 mm (1.5" x 0.05")	38 mm x 25 mm x 2 mm (1.49" x 0.98" x 0.07")	2180 mm (85.82")	200 mm (7.87")	185°	900
	SB-63NC	63.5 mm x 2.5 mm (2.5" x 0.09")	63.5 mm x 1.6 mm (2.5" x 0.06")	60 mm x 30 mm x 3.2 mm (2.36" x 1.18" x 0.12")	2600 mm (102.36")	250 mm (9.84")	185°	1,650
	SB-80NC (hasta 90 mm)	88.9 mm x 2.3 mm (3.5" x 0.09")	76.2 mm x 2.2 mm (3" x 0.08")	75 mm x 45 mm x 3.2 mm (2.95" x 1.77" x 0.12")	2850 mm (112.2")	250 mm (9.84")	185°	3,150
	SB-110NC	110 mm x 2.8 mm (4.33" x 0.11")	101.6 mm x 4 mm (4" x 0.15")	76.2 mm x 76.2 mm x 2.2 mm (3" x 3" x 0.08")	3600 mm (141.73")	400 mm (15.74")	190°	7,200
	SB-130NC	127 mm x 4 mm (5" x 0.15")	120 mm x 3 mm (4.72" x 0.11")	101.6 mm x 101.6 mm x 3 mm (4" x 4" x 0.11")	5200 mm (204.72")	500 mm (19.68")	190°	10,000
	SB-168NC	168 mm x 6.8 mm (6.61" x 0.26")	168 mm x 4.3 mm (6.61" x 0.16")	127 mm x 127 mm x 6.8 mm (5" x 5" x 0.26")	7000 mm (275.59")	600 mm (23.62")	190°	16,000