


Complete Solution for Tube and Pipe

AUTO SERIES

CNC 2 Axis with NC Hydraulic Bending

Capacity up to Ø88.9mm





Machine Features :

- \bullet CNC bending machine with capacities from 0.D.10mm \sim 90mm
- Fully Automatic and Cost Effective
- Equipped with 3 programmable axis
- Feeding Electric Servo
- Rotation Electric Servo
- Bending Hydraulic (NC)
- Standard with hydraulic pressure die assist
- Equipped with Wiper, Clamping and Pressure Die Seats

- Programmable early mandrel extraction system
- Touch screen system and mobile control
- Quick tool change system
- \bullet NC programmable hydraulic bending precision up to +/- 0.2°
- Automatic springback compensation
- Data input by XYZ or YBC coordinates
- Data storage and editing for multiple files
- Automatic mandrel lubricating system (Optional)

Specifications \ Model	SB-39AUTO	SB-63AUTO	SB-90AUTO
Mild Steel Capacity (mm) (CLR 1.5D)	Ø 38.1mm x 2.0t	Ø 63.5mm x 2.5t	Ø 88.9mm x 2.3t
Stainless Capacity (mm) (CLR 1.5D)	Ø 38.1mm x 1.4t	Ø 63.5mm x 1.6t	Ø 76.2mm x 2.2t
Max. Feeding Stroke (mm) (*)	1800	2030	2350
Max. Tube Length With Mandrel (mm) (*)	2650	3200	3800
Max. Bending Radius (mm) (*)	200	250	250
Max. Bending Angle	190°	190°	190°
Bending Accuracy	±0.2°	±0.2°	±0.2°
Rotation Accuracy	±0.15°	±0.15°	±0.15°
Feeding Accuracy	±0.25mm	±0.25mm	±0.25mm
Machine Dimension (mm) (L x W x H)	3500 × 1160 × 1120	4370 × 1240 × 1170	5100 x 1700 x 1200
Gross Weight (Kg)	1800	4500	6500

⁽ st) Can be extended by request

Due to continuous improvements and designs: the manufacturer reserves the right to modify or make any change of all models without notice.



SOCO MACHINERY CO., LTD.

NO.3, JINGKE E. RD., NANTUN DIST., TAICHUNG CITY 40852, TAIWAN $T:886\text{-}4\text{-}23591888 \ F:886\text{-}4\text{-}23592386$

E : sales@soco.com.tw

