

# Drill Presses – DP-1500VS

## SPECIFICATIONS – DP-1500VS

Drill Capacity		
Steel	1.5"	38 mm
Cast Iron	1.75"	45 mm
Tapping Capacity		
	.937"	24 mm
Spindle Speed		
High	245 – 2000 rpm	
Low	85 – 540 rpm	
Spindle Taper		
	MT 4	
Spindle Travel		
	5.9"	150 mm
Spindle Nose to Table		
	22.75"	580 mm
Spindle Nose to Base		
	40.75"	1035 mm
Quill Diameter		
	2.95"	75 mm
Quill Feed (3-speeds)		
	.0078", .004", .002" per rev.	.2 mm, 1 mm .05 mm per rev.
Column Diameter		
	4.52"	115 mm
Table Dimension (L x W)		
	22" x 18.5"	560 mm x 470 mm
Table Slot		
	.625"	16 mm
Base Dimensions (L x W)		
	27" x 19"	685 mm x 485 mm
Motor		
Main	2 hp	
Coolant	1/8 hp	
Power Requirements		
	220V / 1-phase	
Shipping Dimensions (L x W x H)		
	40" x 25" x 83"	1016 x 635 x 2108 mm
Shipping Weight		
	902 lbs.	410 kgs.

Specifications subject to change without notice.

- ◆ 1-1/2" thru mild steel
- ◆ Variable-speed inverter-driven head
- ◆ 3-speed power down feed
- ◆ Utilizes MT No.4 spindle taper
- ◆ Auto reverse tapping feature
- ◆ Digital RPM readout
- ◆ Integrated coolant system
- ◆ Includes drill chuck
- ◆ Power down feed for drilling
- ◆ 220V 1-phase



SCAN FOR MORE INFORMATION