

# Magnetic Drills – MD-3500 / MD-6000

SPECIFICATIONS – MD-3500		
Maximum Stroke	7.5"	190 mm
Annular Cutter Capacity	1/2" – 1-3/8"	12 mm – 35 mm
Cutter Depth	2"	50 mm
Twist Drill Capacity	1/16" – 1/2"	1.5 mm – 13 mm
Spindle Holder	3/4"	19 mm
No Load RPM	595	
Magnetic Adhesion	13000N	
Power Requirements	110V 60hz	
Shipping Weight	40 lbs.	18 kgs.

Specifications subject to change without notice.

- ◆ 1-3/8" maximum cutter capacity
- ◆ 2" maximum cutter depth
- ◆ Gravity coolant system
- ◆ 595 RPM
- ◆ 3/4" spindle
- ◆ 7.5" stroke
- ◆ Includes drill chuck
- ◆ 110V

- ◆ 2-3/8" maximum cutter capacity
- ◆ 3" maximum cutter depth
- ◆ Gravity coolant system
- ◆ Two speed with reverse
- ◆ 3/4" spindle
- ◆ 8.25" stroke
- ◆ 110V

SPECIFICATIONS – MD-6000		
Maximum Stroke	8.25"	210 mm
Annular Cutter Capacity	1/2" – 2-3/8"	12 mm – 60 mm
Cutter Depth	3"	75 mm
Twist Drill Capacity	3/32" – 5/8"	2.5 mm – 16 mm
Spindle Holder	3/4"	19 mm
No Load RPM (low/high)	260/460	
Magnetic Adhesion	18000N	
Power Requirements	110V 60hz	
Shipping Weight	64 lbs.	29 kgs.

Specifications subject to change without notice.



MD-3500



SCAN FOR MORE INFORMATION

OPTIONAL TOOLING	
SKU	Description
1000330	9/16" OD TiN Coated Annular Cutter, 2" Cutting Depth, 3/4" Shank
1000331	11/16" OD TiN Coated Annular Cutter, 2" Cutting Depth, 3/4" Shank
1000332	13/16" OD TiN Coated Annular Cutter, 2" Cutting Depth, 3/4" Shank
1000333	15/16" OD TiN Coated Annular Cutter, 2" Cutting Depth, 3/4" Shank
1000334	1" OD TiN Coated Annular Cutter, 2" Cutting Depth, 3/4" Shank
1000335	1-1/16" OD TiN Coated Annular Cutter, 2" Cutting Depth, 3/4" Shank
1000336	2" OD TiN Coated Annular Cutter, 2" Cutting Depth, 3/4" Shank
1000337	Complete Set of 6 TiN Coated Annular Cutter, 2" Cutting Depth, 3/4" Shank.



MD-6000



SCAN FOR MORE INFORMATION