

Turning Roll Positioners – RWP-55 / RWP-110



RWP-55

- ◆ 5.5 ton capacity (RWP-55)
- ◆ 11 ton capacity (RWP-110)
- ◆ Perfect for welding, polishing, glue-lining, and assembling
- ◆ Dual drive wheels
- ◆ Dual idler wheels
- ◆ AC inverter driven
- ◆ Self-aligning
- ◆ Conventional style with rubber drive wheels
- ◆ 220V 3-phase



SCAN FOR MORE INFORMATION

SPECIFICATIONS – RWP-55		
Maximum Load Capacity	9,900 lbs.	4500 kgs.
Minimum Diameter	9.8"	250 mm
Maximum Diameter	90"	2300 mm
Rotation Speed	19–196 fpm	6–60 mpm
Total Rollers	4	
Drive Rollers	2	
Rubber Roller Diameter	9.8"	250 mm
Rubber Roller Width	3.93"	100 mm
Steel Roller Diameter	9.44"	240 mm
Steel Roller Width	.78"	20 mm
Speed Control	AC Inverter	
Number of Motors	2	
Motor KW	0.37	
Shipping Dimensions (L x W x H)	69" x 30" x 44"	1750 mm x 750 mm x 1100 mm
Total Weight of Unit	1,320 lbs.	600 kgs.

Specifications subject to change without notice.



RWP-110



SCAN FOR MORE INFORMATION

SPECIFICATIONS – RWP-110		
Maximum Load Capacity	19,800 lbs.	9,000 kgs.
Minimum Diameter	12.5"	320 mm
Maximum Diameter	110"	2800 mm
Rotation Speed	19–196 fpm	6–60 mpm
Total Rollers	4	
Drive Rollers	2	
Rubber Roller Diameter	11.8"	300 mm
Rubber Roller Width	4.72"	120 mm
Steel Roller Diameter	11.4"	290 mm
Steel Roller Width	1"	25 mm
Speed Control	AC Inverter	
Number of Motors	2	
Motor KW	0.55	
Shipping Dimensions (L x W x H)	77" x 32" x 78"	1950 mm x 800 mm x 1200 mm
Total Weight of Unit	1,606 lbs.	730 kgs.

Specifications subject to change without notice.