

# Shears – SH-5210 / SH-5214

## SPECIFICATIONS – SH-5210

Shear Length	52"	1321 mm
Thickness (SS)	10 ga. (13 ga.)	
Minimum Thickness	24 ga.	
Front Gauge Length	24"	609 mm
Back Gauge Length	24"	609 mm
Strokes per Minute	28	
Blade Angle	1°	
Motor	5 hp	
Power Requirements	220V 1-Phase	
Shipping Dimensions (L x W x H)	75" x 36" x 53"	1905 x 914 x 1346 mm
Shipping Weight	3,000 lbs.	1364 kgs.

Specifications subject to change without notice.

- ◆ 52" x 10-gauge mild steel capacity
- ◆ Back and side gauges
- ◆ 5 HP motor
- ◆ 26 strokes per minute
- ◆ Multi-sided blades
- ◆ Front support arms
- ◆ 220V 1-phase

- ◆ High-carbon, high-chromium blades with hold downs
- ◆ Back and side gauges
- ◆ 3 HP motor
- ◆ 35 strokes per minute
- ◆ Multi-sided blades
- ◆ 220V 1-phase

## SPECIFICATIONS SH-5214

Shear Length	52"	1321 mm
Thickness (SS)	14 ga. (18 ga.)	
Minimum Thickness	24 ga.	
Front Gauge Length	24"	609 mm
Back Gauge Length	24"	609 mm
Strokes per Minute	35	
Blade Angle	1°	
Motor	3 hp	
Power Requirements	220V 1-Phase	
Shipping Dimensions (L x W x H)	74" x 36" x 53"	1880 x 914 x 1346 mm
Shipping Weight	1,900 lbs.	864 kgs.

Specifications subject to change without notice.

