

Vertical Mill/Drill – VMD-828G



SPECIFICATIONS – VMD-828G

Drilling Cap. Cast Iron	1.5"	40 mm
Drilling Cap. Mild Steel	1.25"	32 mm
Face Mill Cap.	3"	76 mm
End Mill Cap.	1.25"	32 mm
Working Table Size	8.25" x 28.75"	210 x 730 mm
Working Table Cross Travel	9"	230 mm
Working Table Longitudinal Travel	19.5"	500 mm
T-Slot Size	.55"	14 mm
Head Tilt Left Right	90°	
Head Swivel	360°	
Spindle Taper	R8	
Maximum Distance Spindle To Base	16.14"	410 mm
Spindle Stroke	4.75"	120 mm
Spindle Speed	90, 210, 345, 670, 1180, 1970 rpm	
Power Supply	115V, 60 hz, 20A	
Main Motor	2 hp	
Coolant Pump	1/16 hp	
Shipping Dimension (L x W x H)	69" x 44" 70"	1753 x 1118 x 1778 mm
Gross Weight	710 lbs.	322 kgs.

Specifications subject to change without notice.

- ◆ 8" x 28" table
- ◆ Gear driven head
- ◆ R8 spindle taper
- ◆ Integrated coolant system
- ◆ Storage cabinet
- ◆ 7/16" x 20" drawbar
- ◆ 110V