

Welding Positioners – WP-1800F



SPECIFICATIONS – WP-1800F

Speed	0 – 6 rpm (Variable)	
Thru Hole (Material OD)	2.25"	57.15 mm
Chuck Capacity	1/4" OD – 12" ID	6.35 OD – 305 ID mm
Chuck Size Three Jaw	8"	203 mm
Maximum Current	300 Amps	
Weight Capacity–Vertical	250 lbs. (113 kgs.)	
Weight Capacity–Horizontal	200 lbs. (91 kgs.) 6" from Chuck	
Weight Capacity–Angled	150 lbs. (68 kgs.) 6" from Chuck	
Drive	Automatic / Manual	
Power	110V, 60hz, 15A	
Motor	220V, 1/8 Hp (90W)	
Shipping Dimensions (L x W x H)	60" x 44" x 68"	1524 mm x 1118 mm x 1727 mm
Shipping Weight	400 lbs.	181 kgs.

Specifications subject to change without notice.

- ◆ Variable speed
- ◆ Automatic and manual modes
- ◆ Foot pedal controlled
- ◆ 1/4" OD to 12" ID capacity
- ◆ 300 Amp maximum
- ◆ 2-1/4" thru-hole
- ◆ Integrated rolling cabinet
- ◆ 110 volt